

TECHNICAL SPECIFICATION 2026

DISCOVERY
SPORT



ENGINES AND TECHNICAL SPECIFICATION

Discovery Sport features advanced engine options, providing new levels of performance, efficiency, and refinement. There is a plug-in electric hybrid (PHEV) engine for all-electric, zero tailpipe emissions driving, as well as diesel options.

1

ENGINES

View the available engines, their fuel economy and specifications.

2

DIMENSIONS AND CAPABILITIES

View the ride height, turning circle and other capability specifications.

ENGINES

ENGINE	PETROL PLUG-IN ELECTRIC HYBRID (PHEV)	
	P270e	■
Plug-in Hybrid Electric Vehicle (PHEV)		
Transmission		Automatic
Driveline	All Wheel Drive (AWD)	
Maximum power (HP / rpm)	269* / 5,000-5,500	
Maximum torque (Nm / rpm)	540* / 2,000 - 3,250*	
Capacity (cc)	1,498	
No. of cylinders / Valves per cylinder	3 / 4	
Cylinder layout	Inline	
Bore / stroke (mm)	83.0 / 92.3	
Compression ratio (:1)	10.5+ / -0.5	
FUEL ECONOMY – WLTP**		
Seating		5
WLTP Consumption	Combined	mpg (l/100 km)
		192.2-174.4 (1.5-1.6)
WLTP CO ₂ Emissions	Combined	(g/km)
		33-36
Fuel tank capacity - useable litres		58

■ Standard – Not Available.

*When combined with electric motor. **The figures provided are as a result of official manufacturer's tests in accordance with GB legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route. CO₂, eAER, and economy figures refer to GB models. The figures for Northern Ireland model may vary - please refer to the NI configurator.

ENGINES

PETROL PLUG-IN ELECTRIC HYBRID (PHEV)	
P270e	
BATTERY AND CHARGING TIMES	
Home Charger / Wall box 7 kW	2 hours 12 minutes to 100%
Rapid DC Charger 32 kW	30 mins to 80%
Domestic Plug 2.3 kW	6 hours 42 minutes to 100%
Battery capacity Total (Usable) kWh	11.975
Charging cable length (m)	5
PERFORMANCE	
Acceleration (secs) 0-60 mph (0-100 km/h)	7.0 (7.4)
Maximum speed mph (km/h)	118 (190)
ELECTRIC MOTOR DATA	
Maximum power HP (kW)	109 (80)
Maximum torque (Nm)	260
EV Range Combined (WLTP*) miles (km)	38-36 (61-58)
EV Range expected Real World data (up to) miles (km)	28 (45)
Brakes	
Front type	Twin piston, sliding caliper, Vented discs
Front diameter (mm)	349
Rear type	Single piston, sliding caliper, Vented discs
Rear diameter (mm)	325
Park brake diameter (mm)	325
WEIGHTS (kg)**	
Unladen weight (EU) [†]	2,168
Unladen weight (DIN) ^{††}	2,093
Gross Vehicle Weight (GVW)	2,750
TOWING (kg)	
Seating	5
Unbraked trailer	750
Maximum towing	Up to 1,600
Maximum coupling point (nose weight)	100
Maximum vehicle and trailer combination	4,350
ROOF CARRYING (kg)	
Maximum roof load (including cross bars) [‡]	75

*The figures provided are as a result of official manufacturer's tests in accordance with GB legislation with a fully charged battery. For comparison purposes only. Real-world figures may differ. CO₂, fuel economy, energy consumption and range figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment, accessories fitted, actual route and battery condition. Range figures are based upon production vehicle over a standardised route. EV Range, eAER and economy figures refer to GB models. The figures for Northern Ireland model may vary - please refer to the NI configurator.

**Weights reflect vehicles to standard specifications. Optional extras increase weight. [†]Includes a 75kg driver, full fluids and 90% fuel. ^{††}Includes full fluids and 90% fuel. [‡]Roof carrying load reduced to 60kg when Summer Tyres are fitted.

ENGINES

ENGINE	DIESEL MILD HYBRID (MHEV)		
	D165	D200	■
Mild Hybrid Electric Vehicle (MHEV)			Automatic
Transmission			All Wheel Drive (AWD)
Driveline			163 / 3,500-4,250
Maximum power (HP / rpm)			380 / 1,500-2,500
Maximum torque (Nm / rpm)			1,998
Capacity (cc)			4 / 4
No. of cylinders / Valves per cylinder			Inline
Cylinder layout			83.0 / 92.3
Bore / stroke (mm)			16.5+ / -0.5
Compression ratio (:1)			
FUEL ECONOMY – WLTP*			
Seating			5 / 5 + 2
WLTP Consumption	Low	mpg (l/100 km)	36.1-34.2 (7.8-8.3) / 34.9-33.5 (8.1-8.4)**
	Medium	mpg (l/100 km)	41.7-39.3 (6.8-7.2) / 40.3-38.5 (7.0-7.3)
	High	mpg (l/100 km)	49.6-47.5 (5.7-6.0) / 48.6-46.8 (5.8-6.0)
	Extra High	mpg (l/100 km)	42.4-40.4 (6.7-7.0) / 41.8-39.8 (6.8-7.1)
	Combined	mpg (l/100 km)	43.1-41.1 (6.5-6.9) / 42.2-40.4 (6.7-7.0)
WLTP CO ₂ Emissions	Low	(g/km)	205-217 / 212-221**
	Medium	(g/km)	178-188 / 184-192
	High	(g/km)	149-156 / 152-158
	Extra High	(g/km)	174-183 / 177-186
	Combined	(g/km)	172-180 / 175-183

■ Standard.

*The figures provided are as a result of official manufacturer's tests in accordance with GB legislation. For comparison purposes only. Real-world figures may differ. CO₂ and fuel economy figures may vary according to factors such as driving styles, environmental conditions, load, wheel fitment and accessories fitted. **When Efficiency Pack fitted.

ENGINES

FUEL ECONOMY – CONTINUED

Fuel tank capacity - useable litres

Diesel Exhaust Fluid (DEF) - useable litres

PERFORMANCE

Seating

Acceleration (secs) 0-60 mph (0-100 km/h)

Maximum speed mph (km/h)

BRAKES

Front type

Front diameter (mm)

Rear type

Rear diameter (mm)

Park brake diameter (mm)

WEIGHTS (kg)*

Seating

Unladen weight (EU)**

Unladen weight (DIN)[†]

Gross Vehicle Weight (GVW)

TOWING (kg)

Seating

Unbraked trailer

Maximum towing

Maximum coupling point (nose weight)

Maximum vehicle and trailer combination

ROOF CARRYING (kg)

Maximum roof load (including cross bars)^{††}

	DIESEL MILD HYBRID (MHEV)	
	D165	D200
Fuel tank capacity - useable litres	65	65
Diesel Exhaust Fluid (DEF) - useable litres	17	17
Seating	5 / 5 + 2	5 / 5 + 2
Acceleration (secs) 0-60 mph (0-100 km/h)	9.5 / 9.8 (10.2 / 10.6)	8.1 / 8.3 (8.6 / 8.9)
Maximum speed mph (km/h)	112 (180)	117 (188)
Front type	Single Piston, sliding caliper, Vented discs (17" wheels) Twin piston, sliding caliper, Vented discs (18"-21" wheels)	Single Piston, sliding caliper, Vented discs (17" wheels) Twin piston, sliding caliper, Vented discs (18"-21" wheels)
Front diameter (mm)	325 (17" wheels) 349 (18"-21" wheels)	325 (17" wheels) 349 (18"-21" wheels)
Rear type	Single piston, sliding caliper, Solid discs / Single piston, sliding caliper, Vented discs	Single piston, sliding caliper, solid discs / Single piston, sliding caliper, vented discs
Rear diameter (mm)	300 / 325	300 / 325
Park brake diameter (mm)	300 / 325	300 / 325
Unladen weight (EU)**	5 / 5 + 2	5 / 5 + 2
Unladen weight (DIN) [†]	1,949 / 2,028	1,949 / 2,028
Gross Vehicle Weight (GVW)	1,874 / 1,953	1,874 / 1,953
Maximum coupling point (nose weight)	2,590 / 2,750	2,590 / 2,750
Maximum vehicle and trailer combination	5 / 5 + 2	5 / 5 + 2
Maximum roof load (including cross bars) ^{††}	75	75

DIMENSIONS AND CAPABILITIES

DIMENSIONS

Maximum height 1,727mm
Overall length 4,597mm
Width 2,069mm mirrors folded
Width 2,173mm mirrors out
Front wheel track 1,625.2mm
Rear wheel track 1,631.3mm
Wheelbase 2,741mm

TURNING CIRCLE

Kerb-to-kerb 11.8m
Wall-to-wall 12.14m
Turns lock-to-lock 2.31



Front wheel track 1,625.2



Maximum height
1,727mm

Width 2,069mm mirrors folded
Width 2,173mm mirrors out

WADING DEPTH

Maximum wading depth 600mm

HEADROOM

Maximum front / rear headroom with standard roof 1,003mm / 984mm
Maximum front / rear headroom with panoramic roof 1,021mm / 984mm

LEGROOM

Maximum front legroom 993mm
Maximum rear legroom second row 968mm
Maximum rear legroom third row 665mm

LOADSPACE CAPACITY

Height 785mm, Width 1,323mm
Loadspace width between arches 1,107mm
5 seats
Length behind first row 1,771mm
Length behind second row 980mm
Maximum loadspace volume behind first row Dry* 1,574 litres, Wet** 1,794 litres
Maximum loadspace volume behind second row Dry* 780 litres, Wet** 897 litres

5 + 2 seats

Length behind first row 1,824mm
Length behind second row 967mm
Length behind third row 225mm
Maximum loadspace volume behind first row Dry* 1,451 litres, Wet** 1,651 litres
Maximum loadspace volume behind second row Dry* 657 litres, Wet** 754 litres
Maximum loadspace volume behind third row Dry* 115 litres, Wet** 157 litres

OBSTACLE CLEARANCE

Standard ride height 172mm
Off-Road ride height 210mm

APPROACH AND DEPARTURE CLEARANCE

Approach Angle - 22.3°
Departure Angle - 28.3°
Ramp Angle - 20.4°^{††}



Overall length 4,597mm



Rear wheel track 1,631.3mm

Weights and dimensions shown apply to standard-specification, unladen vehicles, which may be affected by optional features and equipment.

*Dry: volume as measured with Verband Der Automobilindustrie-compliant solid blocks (200mm x 50mm x 100mm). **Wet: volume as measured by simulating the loadspace filled with liquid. Figures are representative of seats fully forward and not tilted. [†]Approach Angle for P270e will be 25.0°. Fitting of side tubes or side steps may affect the off-road capability of the vehicle. Challenging off-road driving requires full training and experience. ^{††}Ramp Angle for P270e will be 19.9°. Fitting of side tubes or side steps may affect the off-road capability of the vehicle. Challenging off-road driving requires full training and experience.

Vehicle shown is a Landmark in Varesine Blue (features fitted market dependent).